

Grade A Non-Fat Dry Milk (SMP) High-Heat

Spore Max 100

Version 1.01

Revision Date: 11/25/2020

Confidential

PRODUCT SPECIFICATION

Skim Milk Powder Milk (SMP) High Heat

Valley Milk, LLC Skim Milk Powder High Heat is made through the spray ball method of drying fresh skimmed, pasteurized cow's milk. All milk that is processed in our facility is collected from our dedicated multigenerational, family owned dairy farms. All of the milk originates from the United States in California's San Joaquin Valley and Skim Milk Powder High Heat has a shelf life of two years from the production date.

PHYSICAL

	MINIMUM	MAXIMUM	UNITS	METHODS
				AOAC
Protein	32.40		%m/m	991.20
Milk Protein in				AOAC
milk Solids				991.20
Non-Fat	34.0	-	%m/m	
Casein Protein	27.0	-	%m/m	AOAC
Moisture	-	4.0	%m/m	AOAC 927.05
Fat	-	1.25	%m/m	AOAC 989.05
Titratable				ADPI/Std. M. 17th
acidity	-	0.15	%m/v	ed.
				ADPI/Std. M. 17th
WPNI	-	1.5	mg/g	ed.
Lactose	-	58.3	%m/v	AOAC 984.22
Ash	-	8.6	%m/v	AOAC 945.46
				ADPI/Std. M. 17th
pH	6.4	7.2	mol/L	ed.
				ADPI/Std. M. 17th
Solubility Index	-	1.25	mL	ed.
		Not		
Foreign matter	-	Detected	/25g	
Scorched				ADPI BUL. 916
particles	-	7.5	mg/25g	

CHEMICAL

	MINIMUM	MAXIMUM	UNITS	METHODS
Antibiotics	-	Negative	Charm S/L	Charm SL3
Aflatoxin M1	-	<0.50	μg/L	Charm

SENSORY

Flavor	Free from objectionable flavors			
Appearance	No notable defect in color or particle			
Color	White to light cream			

MICROBIOLOGICAL

	MINIMUM	MAXIMUM	UNITS	METHODS
Aerobic Plate		<10,000	cfu/g	AOAC
Count	-	<10,000	ciu/g	990.12
Yeast & Mold	-	<50	cfu/g	BAM Ch 18
Coliforms	-	<10	cfu/g	AOAC 991.14
Thermophilic		<100	Cfu/q	CMMEF Ch. 25
Spores		100	Ciu/g	
Escherichia coli	-	<3	MPN/g	BAM Ch 4
Coagulase-				AOAC
Positive	-	Negative	cfu/g	2003.08
Staphylococci				
Salmonella	-	Absent	/375g	AOAC-RI 121501
Listeria	-	Negative	/25g	AOAC-RI 061702



PACKAGING

Product may be packaged in either heat sealed poly-lined multiwall kraft paper bags or packaged into poly lined totes without the use of staples or metal fasters.



STORAGE AND HANDLING

It is recommended that product is stored at 80°F or less, with relative humidity of 65% or less, and in an odor-free environment. Stocks should be used in rotation preferably within 24 months of manufacture or as dictated by the expiration date labeled on the product.

